

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**IN THE CLAIMS:**

1. (CURRENTLY AMENDED)A setpoint correction method for an electrically controlled slave axis which, in accordance with a predefined functional relationship follows a guide movement of a higher-order guide axis comprising the steps of:  


---

- increasing a position measured value of the guide axis for driving the slave axis by a position correction value which is determined proportionally to the guide axis's speed, and  


---

- ~~determining a constant value for said guide axis's speed being assumed to be substantially constant~~ during a data propagation time of the position measured value of the guide axis.
  
2. (CURRENTLY AMENDED)A setpoint correction method for an electrically regulated slave axis which, in accordance with a predefined functional relationship follows a guide movement of a higher-order guide axis comprising the steps of:  


---

- increasing a position measured value of the guide axis for driving the slave axis by a position correction value which is determined proportionally to the guide axis's speed, and  


---

- ~~determining a constant value for said guide axis's speed being assumed to be substantially constant~~ during a data propagation time of the position measured value of the guide axis and a delay of a position control system of the slave axis.
  
3. (ORIGINAL)The setpoint correction method according to claim 1 or 2, wherein the position correction value is determined so as to compensate for a lag error of the slave axis.
  
4. (ORIGINAL)The setpoint correction method according to claim 1, further comprising connecting a rotary encoder to the guide axis supplying a guide axis angle and increasing said guide axis angle by a correction angle which is proportional to the guide axis's

angular velocity and weighted with the data propagation time of the position measured value of the guide axis said correction angle being determined as follows:  $\phi_{\text{corr}} = \omega_L * T_T$ , wherein  $\phi_{\text{corr}}$  is the position correction value, namely a correction angle,  $\omega_L$  is the speed of the guide axis, namely an angular velocity and  $T_T$  is the data propagation time.

5. (ORIGINAL)The setpoint correction method according to claim 2, further comprising connecting a rotary encoder to the guide axis supplying a guide axis angle and increasing said guide axis angle by a correction angles which is proportional to the angular velocity of the guide axis and weighted with the data propagation time of the position measured value of the guide axis and a delay of the position control system of the slave axis, said correction angle being determined as follows:  $\phi_{\text{corr}} = \omega_L * (T_T + T_R)$ , wherein  $\phi_{\text{corr}}$  is the position correction value, namely a correction angle,  $\omega_L$  is the speed of the guide axis, namely an angular velocity,  $T_T$  is the data propagation time, and  $T_R$  is the delay.
6. (ORIGINAL)The setpoint correction method according to claim 4 or 5, further comprising determining the angular velocity of the guide axis by differentiating guide axis angles.
7. (CURRENTLY AMENDED)The setpoint correction method according to claims 1 ~~and or~~ 2, further comprising using a busy system to enable the guide axis and the slave axis to communicate, and wherein the data propagation time represents the transmission time of the position measured values of the guide axis via a data bus.
8. (CURRENTLY AMENDED)A control system for generating and correcting setpoints for driving a slave axis which, in accordance with a predefined functional relationship follows a guide movement of a higher-order guide axis comprising a register for registering position measured values of the guide axis, said register generating and applying position correction values to position measured values wherein the position correction values are determined proportionally to the guide axis's speed, wherein a constant value of said guide axis's speed being assumed to be substantially constant is

- used during a data propagation time of the position measured value of the guide axis and/or a delay of a position control system of the slave axis.
9. (ORIGINAL)The control system according to claim 8, wherein position correction values are determined so as to compensate for a lag error of the slave axis.
  10. (ORIGINAL)The control system according to claim 8, wherein the register is a rotary encoder which supplies guide axis angles.
  11. (ORIGINAL)The control system according to claim 10, wherein registered guide axis angles can be increased by correction angles which are proportional to the guide axis's angular velocity and weighted with the data propagation time of the position measured value of the guide axis, said correction angles to be determined as follows:  $\varphi_{\text{corr}} = \omega_L * T_T$ .
  12. (CURRENTLY AMENDED)The control system according to claim 10, wherein registered guide axis angles can be increased by correction angles which are proportional to ~~the~~an angular velocity of the guide axis's ~~velocity~~ and weighted with the delay of the position control system of the slave axis, it being possible for said correction angles to be determined as follows:  $\varphi_{\text{corr}} = \omega_L * T_R$ .
  13. (ORIGINAL)The control system according to claim 8, further differentiating the guide axis angles and wherein an angular velocity of the guide axis can be derived.
  14. (ORIGINAL)The control system according to claim 8, further comprising a bus system by which the guide axis and the slave axis communicate, and wherein the data propagation time represents the transmission time of the position measured values of the guide axis via a data bus.

15. (NEW) A setpoint correction method for an electrically controlled slave axis which, in accordance with a predefined functional relationship follows a guide movement of a higher-order guide axis comprising the step of:
  - increasing a position measured value of the guide axis for driving the slave axis by a position correction value which is determined proportionally to the guide axis's speed.
16. (NEW)The setpoint correction method according to claim 15, further comprising the step of determining a constant value for said guide axis's speed during a data propagation time of the position measured value of the guide axis.
17. (NEW)The setpoint correction method according to claim 15, wherein the position correction value is determined so as to compensate for a lag error of the slave axis.
18. (NEW)The setpoint correction method according to claim 15, further comprising connecting a rotary encoder to the guide axis supplying a guide axis angle and increasing said guide axis angle by a correction angle which is proportional to the guide axis's angular velocity and weighted with the data propagation time of the position measured value of the guide axis said correction angle being determined as follows:  $\varphi_{\text{corr}} = \omega_L * T_T$ , wherein  $\varphi_{\text{corr}}$  is the position correction value, namely a correction angle,  $\omega_L$  is the speed of the guide axis, namely an angular velocity and  $T_T$  is the data propagation time.
19. (NEW)The setpoint correction method according to claim 18, further comprising determining the angular velocity of the guide axis by differentiating guide axis angles.
20. (NEW)The setpoint correction method according to claims 15, further comprising using a bus system to enable the guide axis and the slave axis to communicate, and wherein the data propagation time represents the transmission time of the position measured values of the guide axis via a data bus.